LIFEBREATH®
INDOOR AIR SYSTEMS

MAX SERIES
HEAT RECOVERY VENTILATORS

Model Selection

Model	Description H x W x D (in)	Airflow cfm (L/s) .1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)	Effectiveness @ 0 ºC (32 ºF)	Performance Highlights
95 MAX*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited for tight installations.
100 ECM*	Recirculating Defrost 19 x 33.62 x 14.75	161 (76)	143 (68)	128 (61)	114 (54)	98 (46)	78%	Same design as 155 MAX, with a highly efficient energy-saving ECM motor.
155 MAX*	Recirculating Defrost 19 x 33.62 x 14.75	184 (87)	163 (77)	146 (69)	132 (62)	115 (54)	84%	Most popular HRV. Horizontal with door port balance. Also available in reverse model 155 MAX RX
205 MAX*	Recirculating Defrost 19 x 33.62 x 15.125	222 (105)	207 (98)	193 (91)	179 (84)	165 (78)	79%	New top port unit for flexible installations, door port balancing.
195 ECM*	Damper Defrost 19 x 49 x 14.75	191 (90)	184 (86)	177 (83)	169 (80)	159 (75)	88%	Dual core for maximum heat recovery and includes highly efficient energy-saving ECM motor.
195 DCS*	Damper Defrost 19 x 49 x 14.75	216 (101)	195 (92)	181 (85)	158 (74)	144 (68)	92%	Dual core for maximum heat recovery and energy efficiency.
300 DCS*	Damper Defrost 19 x 49 x 14.75	232 (110)	212 (100)	202 (96)	183 (86)	163 (77)	90%	Same design as 195 DCS except for greater airflows. Meets the needs of high-efficiency in larger homes.



Control Options



Lifestyle MAX Digital Control #99-DXPL01 **(included)**

- 5-speed operation
- 4 user operational modes
  - continuous ventilation
  - 20 min. ON, 40 min. stand-by
  - 20 min. ON, 40 min. recirculation*
  - continuous recirculation*
  - high speed override
- Built-in interface to furnace
- Automatic service reminder

or choose...



Lifestyle MAX Programmable Control #99-LS01

- **DELUXE** fully featured 5-speed, 4 mode unit.
- Fully **PROGRAMMABLE**, allowing you to customize for your specific lifestyle.
- Dehumidstate Disable

** Not available on all models*

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes



HVI 2100 CERTIFIED

* This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.

AIRIA BRANDS INC.

Visit us at www.lifebreath.com

Manufacturer reserves the right to change specifications without notice.

LIFEBREATH®
INDOOR AIR SYSTEMS

RNC SERIES
HEAT RECOVERY VENTILATORS

Model Selection

Model	Description H x W x D (inches)	Airflow cfm (L/s) .1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)	Effectiveness @ 0 ºC (32 ºF)	Performance Highlights
RNC 95*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited for tight installations.
RNC5-TPD	Recirculating Defrost 18.75 x 27 x 15	169 (60)	156 (73)	149 (70)	136 (64)	126 (59)	74%	Compact unit with door port balancing, Adjustable high speed (3) settings.
RNC5-TPF	Fan Defrost 18.75 x 27 x 15	174 (82)	165 (77)	154 (73)	143 (67)	132 (62)	75%	Compact unit with door port balancing, Adjustable high speed (3) settings.
RNC 120F	Fan Defrost 18.25 x 28.75 x 9.25	152 (72)	141 (67)	131 (62)	122 (58)	114 (54)	71%	Low profile cabinet at only 9.25 inches tall. Fits in bulk and drop ceiling.
RNC 155*	Recirculating Defrost 19 x 33.62 x 14.75	184 (87)	163 (77)	146 (69)	132 (62)	115 (54)	84%	Horizontal model, with door port balancing. One of our most popular units.
RNC 205*	Recirculating Defrost 19 x 33.62 x 15.125	222 (105)	207 (98)	193 (91)	179 (84)	165 (78)	79%	New top port unit for flexible installations, door port balancing.
RNC 10	Damper Defrost 19 x 33.62 x 14.75	177 (83)	164 (77)	156 (73)	143 (67)	123 (58)	76%	Horizontal model with 5 ports and damper defrost. Best value for new construction.
RNC 20	Damper Defrost 19 x 33.62 x 14.75	214 (101)	206 (97)	193 (91)	184 (87)	170 (80)	67%	Same design as RNC 10. Ideally suited to larger applications.



2100 HVI CERTIFIED

* This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.

Control Options



Lifestyle Dehumidistat #99-DH01

- Initiates high speed ventilation when the indoor humidity level is above the set point.



Lifestyle RNC Ventilation Control #99-BC01

- 2 Speed operation
- Standby
- Unit On/Off
- Dehumidistat



Lifestyle RNC Digital Control #99-DX01

- 4 selectable operational modes*
  ** Not available on all models*
- 2 speed operation on each mode
- Adjustable dehumidistat function
- Dehumidistat disable
- High speed override

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes

Accessories

- Weatherhoods - 5”, 6” or 7”
- Kitchen Grille - 6” x 10”
- Tech Grilles – 4”, 5”, 6” or 8”

AIRIA BRANDS INC.

Visit us at www.lifebreath.com

Manufacturer reserves the right to change specifications without notice.

Printed in Canada 98-MAX-RNC (10-13)