

COMMERCIAL

HEAT RECOVERY VENTILATORS

Our commercial heat-recovery solutions can help you breathe a little easier. Constructed to provide maximum efficiency, conserve energy, and improve overall air quality, Lifebreath® HRVs can help you, your business, or your facility breathe a little easier.

Quiet, compact, and powerful Lifebreath commercial heat recovery ventilators are perfect for use in a wide variety of commercial facilities, including commercial office settings, schools, restaurants and night clubs, pool enclosures, or any number of other retail and medical environments.

On the reverse side of this sheet, we've provided a basic overview of the commercial HRV options available. For full details, visit Lifebreath at:

www.lifebreath.com



650 FD

Setting a new standard for energy efficient, clean air homes and businesses.

LIFEBREATH®

INDOOR AIR SYSTEMS

LIFEBREATH® INDOOR AIR SYSTEMS

COMMERCIAL

HEAT RECOVERY VENTILATORS

Model Selection

Indoor Use Model		Effectiveness @ 0 °C	Dimensions H x W x D (in)	Product Features
	**350 DCS 350 DCS-REV**	95%	18.750 (H) 48.000 (W) 28.250 (D)	Airflow up to 400 CFM*; Highly efficient dual core system features a low profile cabinet designed for installations above suspended ceilings. Digital wall control included
	**455 FD 455 DD**	65%	25.625 (H) 28.750 (W) 29.625 (D)	Airflows up to 450 CFM*; Compact and reliable unit for installation in tight locations. Available in damper defrost (DD) or fan defrost (FD).
	**650 FD 650 DD**	80%	24.625 (H) 46.750 (W) 41.500 (D)	Airflow up to 650 CFM*; Two sets of cores in series allows for high efficiency transfer of energy between airstreams. Low profile cabinet allows for installations above suspended ceilings. Available in fan defrost (FD) or damper defrost (DD)
	**700 FD 700 DD**	65%	25.625 (H) 28.750 (W) 29.625 (D)	Airflow up to 700 CFM*; Compact and reliable unit for installation in tight locations. Available in or fan defrost (FD) or damper defrost (DD).
	1200 FD 1200 DD	60%	25.625 (H) 28.750 (W) 29.625 (D)	Airflows up to 1200 CFM*; Compact and reliable unit for installation in tight locations. Available with fan defrost (FD) or damper defrost (DD)
	**700 POOL**	65%	31.250 (H) 30.500 (W) 28.750 (D)	Airflow up to 700*; Designed for indoor pool applications this compact unit delivers installation and operating costs to be less than alternative dehumidification systems. Includes remote dehumidistat.
	1200 POOL	60%	31.250 (H) 30.500 (W) 28.750 (D)	Airflow up to 1200*; Designed for indoor pool applications this compact unit delivers installation and operating costs to be less than alternative dehumidification systems. Includes remote dehumidistat.

Model Selection

Indoor or Outdoor Use Model		Effectiveness @ 0 °C	Dimensions H x W x D (in)	Product Features
	**1500I-ECM 1500E-ECM**	65%	IFD: 37 x 66.75 x 44 EFD: 41 x 69.5 x 46.5 (includes EFD base)	Airflows up to 1500 CFM*; This high efficient unit features brushless DC motors producing quiet, long lasting operation while reducing energy costs. Available in interior (I) or exterior (E) models with standard fan defrost. Various duct configurations and voltage options available.
	**2000 IFD 2000 EFD**	70%	IFD: 47 x 89.9 x 38.4 EFD: 47 x 89.9 x 38.4 (includes EFD base)	Airflows up to 2500 CFM*; Fan defrost unit designed for interior (I) or exterior (E) installations. Various duct configuration and voltage options available.
	**2500 IFD 2500 EFD**	65%	IFD: 39 x 66.75 x 57.25 EFD: 43 x 69.5 x 59.75 (includes EFD base)	Airflows up to 2600 CFM*; 3 speed fan defrost unit designed for interior (I) or exterior (E) installations. Various duct configuration and voltage options available.

*Refer to model specifications for design information. Specifications are available at www.lifebreath.com

**Manufacturer reserves the right to change specifications without notice.

ISO 9001 REGISTERED

511 McCormick Blvd.
London, Ontario, Canada N5W 4C8
Ph: (519) 457-1904

Toll Free: 1-855-AIRIA-00
(1-855-247-4200)

www.lifebreath.com

AIRIA BRANDS INC.